


## **OHV COUNTER** Generation 4.1

## **Key Info**

- For off-highway vehicles (ATVs, quads, dirt bikes, etc.)
- Advanced microelectronic design
- Self-contained design; no external wires or tubes
- Designed to be buried
- Small and easy to hide reduces vandalism risk
- Long battery life (up to 9 months)
- Large storage capacity (millions of counts)
- Built for outside: -40C (-40F) to +55C (131F)
- Low installation, operating, and maintenance costs
- Field-proven, Generation 4 design (>10 year history)




### TRAFx Counting System

#### TRAFx Dock

To download counters in the field (without PC)

To configure counters (with PC)



## TRAFx DataNet

To view and manage your data



To produce professional reports in seconds.



Try the free Demo at www.trafx.net



Compact, Unobtrusive Design

The TRAFx OHV Counter detects and counts off-highway vehicles such as ATVs, quads, motorcycles, jeeps, 4x4s, etc. It is the first, and currently the only OHV counter available. Because the counter is small (about the size of a bar of soap), it is easy to deploy and hide. It is designed to be buried and left unattended in the field for long periods. It can also be mounted under a bridge, or hidden under a log or rock at the trailside.

#### Easy to Deploy

Each TRAFx OHV Counter combines an aerospace-quality magnetometer with advanced embedded processing software to produce a state-of-the-art, small, battery-efficient, easy to hide and deploy counter built for the outdoor environment. It uses three standard "C size" alkaline batteries.














Generation 4.1

(Bird's eye view)



Detection range, as shown below, is primarily a function of vehicle size.

Dirt bikes (and snowmachines) = 1 to 2m (3.3 to 6ft) Quads = 2 to 3m (6.6 to 10ft)Highway vehicles (e.g., jeeps) = up to 6m (20ft)

- To detect both smaller OHVs (e.g., quads) and larger OHVs (e.g., jeeps), install the counter within range of the smaller vehicle type (i.e., quads).
- · The detection zone extends out in all directions from the counter, whether the counter is placed above or below around.
- · If only a portion of an OHV enters the detection zone, it will be detected.







#### **FEATURES**

- · Hourly or daily totals, or timestamps
  - -14 000 hourly or daily totals = > 400 million counts
  - -14 000 timestamps
- Flexible installation options (see above)
- · Proprietary design for detecting small vehicles
- User programmable modes/settings
  - -Programmable settings include:
    - \*Real-time clock
      - \*Start date/time
    - \*Detection range
- \*Digital sampling parameters
- \*Delay after event \*Site/counter name
- Three colour-coded LEDs indicate status of operation -green light flashes upon detection
- Digital readout of battery voltage level (e.g., 4.2V)
- · Automatic low battery warning
- User replaceable parts
- · Engineered and built in the Canadian Rockies

# "3-in-1 design!"

#### TRAFX VERSATILITY

The TRAFx OHV Counter comes pre-programmed and ready to use as the TRAFx Vehicle Counter or the TRAFx Mountain Bike Counter, at no extra charge. Simply change the mode when configuring the counter.

Also, it can be quickly and easily converted to the TRAFx Infrared Trail Counter by ordering a special conversion kit.

Visit www.trafx.net for details.

#### SPECIFICATIONS

CASE: 14cm x 10.5cm x 5cm (5.5in x 4.1in x 2in); weatherproof

WEIGHT: 250g (8.8oz) (without batteries)

POWER: Three "C size" alkaline batteries (e.g., Energizer) BATTERY LIFE: 8 to 9 months max. with three C alkalines 20 months max. with one D lithium (custom.)

DETECTION RANGE: see box above DATA TYPE: ASCII; .txt file type

DIGITAL MEMORY DESIGN: Data and settings are retained even

when batteries are replaced or die

TIME KEEPING: Quartz clock; 10ppm accuracy @ 20C OPERATING TEMPERATURE: -40C (-40F) to +55C (131F)

SENSOR TYPE: Low-field geomagnetic

COMMUNICATIONS: RS232 serial; 115,000 baud

OTHER: Gold (ENIG) circuitboard; two coats silicon (anti-moisture);

ESD protection and short circuit protection; RoHS (lead-free) LIMITED WARRANTY: 1 year; covers manufacturing defects.

EMI COMPLIANCE: FCC, IC, CE

#### ACCESSORIES/OPTIONS

- LCD tally display
- Extended 5-year warranty
- IR conversion kit

#### TRAFx Research Ltd.

20 MacDonald, Canmore, Alberta, Canada T1W 2N1

T: (403) 678 1802 F: (403) 451-1561

E: info@trafx.net www.trafx.net

